



(19)

(11) Publication number: **58**

Generated Document.

PATENT ABSTRACTS OF JAPAN(21) Application number: **57086626**(51) Intl. Cl.: **H01L 21/30**(22) Application date: **24.05.82**

(30) Priority:	(71) Applicant: HITACHI LTD
(43) Date of application publication: 29.11.83	(72) Inventor: OBAYASHI HIDEHITO MIURA YOSHITSUGU KIMURA TAKESHI MOCHIJI KOZO
(84) Designated contracting states:	(74) Representative:

**(54) MASK FOR X-RAY
LITHOGRAPHY**

(57) Abstract:

PURPOSE: To obtain a mask for X-ray lithography which is reduced in alignment errors, excellent in chemical resistance and transparent to even a visible light, by employing a thin film constituted by diamond or a mixture of diamond and amorphous carbon.

CONSTITUTION: Since diamond has the highest thermal conductivity in the known materials, the employment of diamond makes it possible to quickly transmits to the outside the heat absorbed by an X-ray absorber, such as Au or the like, which is formed on a transparency, and minimize the rise in temperature of a mask due to exposure. As a result, it is possible to prevent any alignment error of a pattern. Moreover, since the mask is constituted by a transparent thin film, a visible light can be employed for alignment. To obtain an X-ray lithography mask, it is effective to form a transparent film

constituted by diamond and amorphous carbon by employing magnetron sputtering or ion beam sputtering. Thus, a mask is obtained which has a sufficiently high film strength and an excellent light-transmitting property.

COPYRIGHT: (C)1983,JPO&Japio